

# JETSETTER®



Jetsetter shown with Platinum shell



Jetsetter shown with Platinum shell /  
Monterey Gray cabinet

<b>Seating Capacity</b>	3 adults
<b>Dimensions</b>	7' x 5'5" x 29"/2.13m x 1.65m x .74m
<b>Water Capacity</b>	200 gallons/750 liters
<b>Weight</b>	475 lbs./215 kg dry; 2,670 lbs./1,205 kg filled*
<b>Spa Shell Options</b>	Alpine White, Crème, Ice Gray, Platinum, Tuscan Sun, or Desert**
<b>Cabinet Options</b>	Everwood®HD: Mocha, Monterey Gray or Teak**
<b>Jets - 14 (w/ Stainless Steel Trim)</b>	1 Moto-Massage® DX jet (2) 1 JetStream® jet 2 Rotary Hydromassage jets 1 Directional Hydromassage jet 4 HydroStream® jets 4 Directional Precision® jets
<b>Water Care System (Optional)</b>	ACE® Salt Water Sanitizing System or EverFresh® System
<b>Jet Pump</b>	Wavemaster® 7000; One-speed, 1.65 HP Continuous Duty, 3.5 HP Breakdown Torque
<b>Circulation Pump</b>	SilentFlo 5000® for quiet, continuous filtration
<b>Effective Filtration Area</b>	90 sq. ft., top loading 100% no-bypass filtration
<b>Ozone System</b>	FreshWater® III Corona Discharge
<b>Control System</b>	IQ 2020® with LCD control panel 115v/20 amp (includes G.F.C.I. protected power cord) or 230v/50amp, 60 Hz***
<b>Lighting System</b>	Luminescence® multi-color four-zone
<b>Heater</b>	No-Fault®, 1500w/115v or 6000w/230v
<b>Energy Efficiency</b>	Certified to the APSP 14 National Standard and the California Energy Commission (CEC) in accordance with California law
<b>Vinyl Cover</b>	3.5" to 2.5" tapered, 1.5 lb. density foam core, with hinge seal in Caramel, Chocolate, Slate, or Evergreen
<b>Cover Lifter (Optional)</b>	CoverCradle®, CoverCradle II, Lift 'n Glide® or UpRite®
<b>Steps (Optional)</b>	Everwood® HD, NXT, or Polymer
<b>Entertainment System (Optional)</b>	Wireless Sound System

\* Includes water and 3 adults weighing 175 lbs. each

\*\*Some color combinations are considered special orders. Ice Gray/Teak, Crème/Monterey Gray, Desert/Monterey Gray, and Platinum/Teak have special order pricing. See your dealer for details.

\*\*\*G.F.C.I. Protected sub-panel required in 230v mode

Export models available in 230v, 50Hz, 1500w Heater

(Wavemaster® 9000; One-speed, 2.5 HP Continuous Duty, 5.2 HP Breakdown Torque), & Tri-X filters



**HotSpring®**

Every day made better®